

TECHNICAL INFORMATION

ClayPeel BLUE Article-No. 8434-3 – ClayPeel SILVER Article-No. 8434-81

ClayPeel blue/silver is a grounding for temporary lacquering of clay models. This lacquer creates a flexible and peelable film on styling clay. After the lacquer has dried, the film can be peeled off without damaging the clay surface of the model.

Ingredients:	waterbased solvent-free synthetic resin
Color:	blue and silver
Temperature range:	max. 30°C/86°F in liquid condition
Storage temperature:	5°C/41°F - 30°C/86°F, avoid temp. below 0°C/32°F
Shelf life:	2 years unopened

Toxicology:	ClayPeel is toxicologically harmless, certified by ACMI, USA.
-------------	---



Drying time:	depends on film thickness and number of layers
Thinner:	thin with water
Clean-up:	remove wet ClayPeel with water. Fully dried ClayPeel can be either peeled off or removed using water and a sponge. Scrub hands with soap and water.

Coverage:	approx. 2 m ² per 750 ml (package) with 2 layers
-----------	---

Sales info:	1 pc = 750 ml; 12 pcs in carton; 360 pcs on pallet
-------------	--

Please note the lacquering recommendations under
www.industrial-products.com/lacquering-recommendations