

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Epoxy Resin L 285

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Epoxy resin products, low in solvents, sensitising

1.3. Details of the supplier of the safety data sheet

Company name:	R&G Faserverbundwerkstoffe GmbH	
	Composite Technology	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49 (0)7157 5304-60	Telefax: +49 (0)7157 5304-70
e-mail:	info@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	

1.4. Emergency telephone number: Vergiftungs-Informations-Zentrale Freiburg
Tel: +49 (0)761 19240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects (skin contact, ingestion).

Suspected of damaging fertility. Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)

1,2,3-Propanetriol, glycidyl ethers

Signal word: Warning**Pictograms:****Hazard statements**

H319 Causes serious eye irritation.

H315 Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 2 of 10

H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects (skin contact, ingestion).
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P321	Specific treatment (see Hazard statements on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	>=50 - <75 %
	500-033-5	603-074-00-8
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H319 H315 H317 H411	
90529-77-4	1,2,3-Propanetriol, glycidyl ethers	>=50 - <75 %
	292-011-4	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Keep respiratory equipment at hand. First Aid for the person providing it can be dangerous to give mouth-to-mouth resuscitation.

After inhalation

Remove person to fresh air and keep comfortable for breathing. Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration. First Aid for the person providing it can be dangerous to give mouth-to-mouth resuscitation. If unconscious place in recovery position and seek medical advice. In case of inhalation of decomposition products in symptoms may be delayed. The affected person may need to be kept under medical observation 48 hours.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

Remove contact lenses, if present and easy to do. Continue rinsing. Chemical burns must be treated promptly by a physician. In the case of complaints or symptoms avoid further impacts. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 3 of 10

After ingestion

Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Risk of aspiration. Potential damage to lungs after vomiting. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints. Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

none known

5.2. Special hazards arising from the substance or mixture

When fire or if heated, a pressure increase will occur and the container may burst. Harmful to aquatic life with long lasting effects. Do not allow to enter into surface water or drains.

Decomposition products may include the following materials: Carbon dioxide (CO₂) Carbon monoxide Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Evacuate all non-essential personnel. No action shall be taken involving any personal risk or without suitable training.

Fire-fighters should: Wear breathing apparatus without recirculating air and suitable protective clothing .

Fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic protection be chemical incidents.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Only allow access to authorised staff. Do not breathe in gases/vapours/aerosols. Provide adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

For emergency responders : Personal protective equipment see Section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. share Pollution of rivers, lakes or sewers, according to local posited that the relevant competent authorities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if environmental impacts caused by the product. (Sewers, waterways, soil or air) The containers from spill area.

6.3. Methods and material for containment and cleaning up

Stop leak if safe to do so. Dilute with plenty of water. Wipe up with absorbent material (eg. cloth, fleece). Absorb with sand, earth, or another absorbent substance.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 4 of 10

6.4. Reference to other sections

Safe handling: see section 7
 Personal protection equipment: see section 8
 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Personal protection equipment: see section 8. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Provide adequate room ventilation, if necessary with vapour extraction at the workplace. Keep only in the original container. Keep receptacles tightly sealed.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Further information on handling

When using do not eat, drink, smoke, sniff. Wash hands with soap and water before eating and drinking. See Section 8, additional information on hygiene measures.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep opened receptacles upright to prevent leakage.

Advice on storage compatibility

Keep away from incompatible substances under § 10.2. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Epoxy resin products, low in solvents, sensitising

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 5 of 10

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light yellow
Odour:	characteristic

Test method

pH-Value (at 20 °C):	not determined
----------------------	----------------

Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	not determined
--	----------------

Flash point:	> 100 °C	ISO 2719
--------------	----------	----------

Flammability

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Lower explosion limits:	not determined
-------------------------	----------------

Upper explosion limits:	not determined
-------------------------	----------------

Ignition temperature:	not determined
-----------------------	----------------

Auto-ignition temperature

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

Not oxidizing.

Vapour pressure:	not determined
------------------	----------------

Density:	1,14 g/cm ³
----------	------------------------

Water solubility:	insoluble
-------------------	-----------

Solubility in other solvents

not determined

Partition coefficient:	not determined
------------------------	----------------

Viscosity / dynamic: (at 25 °C)	600 - 900 mPa·s	ISO 9371
------------------------------------	-----------------	----------

Vapour density:	not determined
-----------------	----------------

Evaporation rate:	not determined
-------------------	----------------

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 6 of 10

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)				
	oral	LD50 11400 mg/kg		Rat	GESTIS
	dermal	LD50 > 22800 mg/kg		Rabbit	GESTIS

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)				
	Acute fish toxicity	LC50 4,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	EPA-660/3-75-009
	Acute algae toxicity	ErC50 9,4 mg/l	72 h	Scenedesmus capricornutum	EPA-660/3-75-009
	Acute crustacea toxicity	EC50 2,8 mg/l	48 h	Daphnia magna	OECD 202
	Acute bacteria toxicity	(> 100 mg/l)	3 h	Activated sludge	

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 7 of 10

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			
	OECD 301F	5%	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			
	OECD 301B	6-12%	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	3,24

BCF

CAS No	Chemical name	BCF	Species	Source
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	31		Quantitative structure-activity relationship (QSAR)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: not persistent.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxydharz)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 8 of 10



Classification code: M6
 Special Provisions: 274 335 601
 Limited quantity: 5 L
 Transport category: 3
 Hazard No: 90
 Tunnel restriction code: E

Other applicable information (land transport)

E1

Inland waterways transport (ADN)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxydharz)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Classification code: M6
 Special Provisions: 274 335 601
 Limited quantity: 5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: 274, 335
 Limited quantity: 5 L
 EmS: F-A, S-F

Other applicable information (marine transport)

E1

Air transport (ICAO)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 9 of 10



Special Provisions:	A97 A158	
Limited quantity Passenger:	30 kg G	
IATA-packing instructions - Passenger:		964
IATA-max. quantity - Passenger:		450 L
IATA-packing instructions - Cargo:		964
IATA-max. quantity - Cargo:		450 L

Other applicable information (air transport)

E1

Passenger-LQ: Y964

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: epoxy resin (number average molecular weight \leq 700), reaction product: bisphenol-A-(epichlorhydrin)

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - water contaminating
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoxy Resin L 285

Print date: 13.11.2017

Product code: 110115

Page 10 of 10

H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects (skin contact, ingestion).
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)