



Technical data sheet

Special thinner standard, colorless

Number:	18-0120-000						
Characteristic:	Solvent blend with flashpoint over 21°C						
Field of application:	To dilute Polyurethane lacquers such as BascoPrime, BascoClear and BascoBase.						
<p>In accordance with the General Conditions of Sale and Delivery, the responsibility of Basler Lacke AG is limited and partially excluded (reference is made to www.basler-lacke.ch). They form an integral part of each supply. In addition, responsibility is declined within the legal limits for any damages resulting of a product being not appropriate for a certain application.</p> <p>We do neither assure nor guarantee the suitability of the products for a certain applicability or a certain type of processing. In either case, the buyer has to do preliminary suitability tests in accordance with his operating conditions.</p>							
Technical information:	<table><tr><td>Processing:</td><td>To adjust the process viscosity</td></tr><tr><td>Density:</td><td>0.89 g/cm³</td></tr><tr><td>Mixing ratio:</td><td>5 - 20%</td></tr></table>	Processing:	To adjust the process viscosity	Density:	0.89 g/cm ³	Mixing ratio:	5 - 20%
Processing:	To adjust the process viscosity						
Density:	0.89 g/cm ³						
Mixing ratio:	5 - 20%						
Processing requirements:	To adjust the process viscosity. Especially if application temperature is over 25°C or if large objects are being coated to improve the absorption of overspray. To adjust the viscosity of lacquers and to clean or degrease substrate and equipment.						
Miscellaneous:	Evaporating time: approx. 40 (Taht means, this liquid nedd x times longer to evaporat than Diethylether.)						
Storage:	12 months from delivery date at +10 - +25 °C, in originally sealed containers. Protect the containers from direct sun light!						