

Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31 V - 2Printing date 10.05.2017 Revision: 10.05.2017 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: PU-S<u>YSTEM H75-AT A-Komponente</u> · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not determined · Application of the substance / the mixture Synthetic resin \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Vosschemie GmbH Esinger Steinweg 50 D-25436 Uetersen Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de · Further information obtainable from: Abteilung Labor / +49 (0)4122 717 0 s.schaller@vosschemie.de · 1.4 Emergency telephone number: Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland Phone: +49 (0)551 19240 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2) GB



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

(Contd. of page 1) · Hazard pictograms · Signal word Warning · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. P302+P352 · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Dungerous components.			
CAS: 25322-69-4	Propane-1,2-diol, propoxylated	20-<25%	
NLP: 500-039-8	♦ Acute Tox. 4, H302		
CAS: 56-81-5	glycerol	3.0-<10%	
EINECS: 200-289-5	substance with a Community workplace exposure limit		
CAS: 616-47-7	1-methylimidazole	1.0-<3.0%	
EINECS: 210-484-7	🛞 Acute Tox. 3, H311; 🔣 Skin Corr. 1B, H314; 🕔 Acute Tox. 4,		
Reg.nr.: 01-2119979544-23	H302		
Additional information. For the wording of the listed has and physics refer to gootion 16			

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

зв



Page 3/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

(Contd. of page 2) • After inhalation: Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation. • After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor. • After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. • 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. • 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available. **SECTION 5: Firefighting measures** · 5.1 Extinguishing media · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet · 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. · 5.3 Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit. · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. **SECTION 6:** Accidental release measures · 6.1 Personal precautions, protective equipment and emergency procedures Particular danger of slipping on leaked/spilled product. Wear protective equipment. Keep unprotected persons away. Avoid contact with the eyes and skin. Ensure adequate ventilation · 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. · 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Page 4/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Avoid contact with the eyes and skin.

Ensure good ventilation/exhaustion at the workplace. Do not inhale gases / fumes / aerosols.

· Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidising agents. Do not store together with acids.

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Store receptacle in a well ventilated area.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

56-81-5 glycerol

WEL (Great Britain) Long-term value: 10 mg/m³

· DNELs

616-47-7 1-methylimidazole

Dermal Long-term exposure - systemic effects 0.42 mg/kg bw/day (worker)

Inhalative Long-term exposure - systemic effects 1.47 mg/m³ (worker)

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Do not eat, drink, smoke or sniff while working.
- Do not inhale gases / fumes / aerosols.
- Store protective clothing separately.
- Immediately remove all soiled and contaminated clothing
- Take off contaminated clothing.
- Wash hands before breaks and at the end of work.
- Use skin protection cream for skin protection.
- Avoid contact with the eyes and skin.

• Respiratory protection:

No special procedures required if all workplace limit values are continuously respected. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

^{· 8.2} Exposure controls



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2017

· Flash point:

· Ignition temperature:

· Explosive properties:

· Auto-ignition temperature:

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

Filter A/P2	(Contd. of page 4)			
• Protection of hands:				
alla				
Protective glove	`S			
	e impermeable and resistant to the product/ the substance/ the preparation.			
Selection of the glove model degradation	aterial on consideration of the penetration times, rates of diffusion and the			
	or to each anewed use of the glove.			
Preventive skin protection	by use of skin-protecting agents is recommended.			
Material of gloves				
DIN EN 374 Nituile mubben NPP				
 Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.35 mm The selection of the suitable gloves does not only depend on the material, but also on further marks of qua and varies from manufacturer to manufacturer. As the product is a preparation of several substances, resistance of the glove material can not be calculated in advance and has therefore to be checked prior to application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to observed. 				
			Value for the permeation: I	Level $\leq 6 \ (\geq 480 \ min)$
			Eye protection:	
			Tightly sealed g	oggles
			Body protection: Protectiv	e work clothing
SECTION 9: Physical	and chemical properties			
· 9.1 Information on basic physical and chemical properties · General Information				
		Appearance:		
Form:	Fluid			
Colour:	Yellowish			
Odour:	Amine-like			
pH-value:	Not determined			
Change in condition				
Initial boiling point and	boiling range: $> 100 \ ^{\circ}C$			

 $> 100 \ ^{\circ}C$

Product is not selfigniting.

vapour mixtures are possible.

Product is not explosive. However, formation of explosive air/

355 °C

(Contd. on page 6) GB



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

		(Contd. of page 5
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1.1 g/cm ³	
· Vapour density	Not determined	
· Solubility in / Miscibility with		
water:	Partly miscible.	
· Partition coefficient: n-octanol/water:	Not determined	
· Viscosity:		
Dynamic at 20 °C:	2000 mPas	
Kinematic:	Not determined	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No decomposition if used according to specifications.

- 10.2 Chemical stability No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions Exothermic polymerisation. Reacts with acids. Reacts with oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	LD/LC50 values relevant for classification:				
Oral	ATE	2092.98 mg/kg (mix) (Calculation method)			
Dermal ATE 43694.8 mg/kg (mix) (Calculation method)					
25322-69-	25322-69-4 Propane-1,2-diol, propoxylated				
Oral	LD50	$500 - \langle 2000 \ mg/kg \ (rat)$			
Dermal	LD50	> 3000 mg/kg (rabbit)			
56-81-5 gl					
$Oral \qquad LD 50 > 2000 \text{ mg/kg (rat)}$					
616-47-7 1-methylimidazole					
Oral	LD50	1144 mg/kg (rat) (OECD 401)			
Dermal	LD 50	> 400 - <600 mg/kg (rabbit) (OECD 402)			
Inhalative $LC0/4h > 1.35 mg/l (rat)$		> 1.35 mg/l (rat)			
•	Primary irritant effect:				
	· Skin corrosion/irritation				
Causes ski	Causes skin irritation.				

(Contd. on page 7) GB



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

V - 2Printing date 10.05.2017 Revision: 10.05.2017 Trade name: PU-SYSTEM H75-AT A-Komponente (Contd. of page 6) · Serious eye damage/irritation Causes serious eye irritation. • Subacute to chronic toxicity: 25322-69-4 Propane-1,2-diol, propoxylated Oral NOAEL (subacute) ≥1000 mg/kg (rat) (OECD 407) · Additional toxicological information: This statement was deduced from the properties of the single components. · Sensitisation No sensitising effects known. · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) · Carcinogenicity No further relevant information available. · Reproductive toxicity/Fertility 25322-69-4 Propane-1,2-diol, propoxylated

Oral NOAEL (fertility) 1000 mg/kg (rat, parents) (OECD 421)

· Reproductive toxicity/Teratogenicity

25322-69-4 Propane-1,2-diol, propoxylated

Oral NOAEL (developmental toxicity) 1000 mg/kg (rat) (OECD 421)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT-single exposure Based on available data, the classification criteria are not met.

 \cdot STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Aquatic toxicity:		
25322-69-4 Propane	-1,2-diol, propoxylated	
EC0/72h	≥100 mg/l (desmodesmus subspicatus) (OECD 201)	
EC50/48h	> 100 mg/l (daphnia) (OECD 202)	
EC50/3h	> 1000 mg/l (activated slugde) (OECD 209)	
LC50/96h	> 100 mg/l (poecilia reticulata) (OECD 203)	
LC50	> 100 mg/l (danio rerio) (48h)	
NOEC (aqua chron.)	≥10 mg/l (daphnia magna) (OECD 211, 21d)	
56-81-5 glycerol		
EC0	> 100 mg/l (bacteria)	
LC50	> 100 mg/l (fish)	
616-47-7 1-methylim	idazole	
EC10	589.6 mg/l (pseudomonas putida) (17h, DIN 38412)	
EC50	1050 mg/l (pseudomonas putida) (17h, DIN 38412)	
EC50/48h	268 mg/l (daphnia magna) (79/831/EWG)	
EC50/72h	180.7 mg/l (scenedesmus subspicatus)	
LC50/96h	> 100 - < 215 mg/l (leuciscus idus) (DIN 38412)	
		(Contd. on page



Page 8/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

	(Contd. of page 7
· 12.2 Persistence and degradability	
25322-69-4 Propane-1,2-diol, propoxylated	
Biodegradation > 60 % (OECD 301 F)	
56-81-5 glycerol	
Biodegradation > 60 % (28d)	
· 12.3 Bioaccumulative potential	
25322-69-4 Propane-1,2-diol, propoxylated	
log Kow 0.3-0.9 (25 °C)	
56-81-5 glycerol	
log Pow -1.75	
616-47-7 1-methylimidazole	
log Pow -0.19 (25 °C)	
· Behaviour in environmental systems:	
· 12.4 Mobility in soil	
25322-69-4 Propane-1,2-diol, propoxylated	

log Koc 0-1

Koc 1-10

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Waste disposal key:

The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· European waste catalogue

07 02 08* other still bottoms and reaction residues

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN-Number		
· ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name		
· ADR, ADN, IMDG, IATA	Void	



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

	(Contd. of page 8	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
· Transport/Additional information:	Not dangerous according to the above specifications.	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- *Information about limitation of use:* Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Relevant phrases H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. Classification according to Regulation (EC) No 1272/2008 Skin. Irrit.2,H315 Eye Irrit.2,H319 	Classification procedure Calculation method Calculation method
 Department issuing SDS: Abteilung Labor Contact: Frau S. Schaller Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Roc Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) 	
Didl. Deriver to Lijer Lever (REACH)	(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: PU-SYSTEM H75-AT A-Komponente

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 • * Data compared to the previous version altered. (Contd. of page 9)

GB