

Type II Component B

01/18 June 2018

:: CHARACTERISTIC

Type II Component B is a solvent-free product based on diphenylmethane-4 4'-diisocyanate (MDI) with higher functional oligomers and isomers. The average functionality is about 2.7.

:: AREA OF APPLICATION

The main application of Type II Component B is hardening polyurethane rigid foams and casting systems.

:: PRODUCT DATA

Material data of the liquid product

Colour brownish

NCO-content 31,8 g/100g (ASTM D 5155-96 A)
Acidity as HCI 150 mg/kg (ASTM D 1638-74)
Viscosity at 20 °C approx. 300 mPa.s (Brookfield)

Density at 20 °C approx. 1.23 g/cm³

Storage (at room temperature and dry) minimum 6 month in the closed original container

:: INSTRUCTION FOR USE

Type II Component B is used for hardening of polyurethane formulations. For further information please refer to the relevant technical data sheet.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE

VOSSCHEMIE GMBH

Esinger Steinweg 50 AMTSGERICHT
25436 Uetersen Pinneberg – HRB 0265 EL
Germany USt-Id-Nr:: DE134800975
www.vosschemie.de ILN: 41 02870 00000 8

SITZ DER GESELLSCHAFT

GESCHÄFTSFÜHRER Dieter Voss, Klaus Voss, Hans-Joachim Rohde

NIEDERLASSUNGEN Ratingen, Oschatz, Kolbermoor Qualitätsmanagement-System zertifiziert von LLOYD'S nach der Qualitätssicherungsnorm DIN EN ISO 9001 : 2015

