

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**5 Min. Epoxy (resin)**

Revision date: 16.03.2018

Product code: 155105

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

5 Min. Epoxy (resin)

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Epoxy resin products, solvent-free, sensitising

**1.3. Details of the supplier of the safety data sheet**

Company name:	R&G Faserverbundwerkstoffe GmbH	
	Composite Technology	
Street:	Im Meißel 7 - 13	
Place:	D-71111 Waldenbuch	
Post-office box:	1145	
	D-71107 Waldenbuch	
Telephone:	+49 (0)7157 5304-60	Telefax: +49 (0)7157 5304-70
e-mail:	info@r-g.de	
Internet:	www.r-g.de	
Responsible Department:	Management	

**1.4. Emergency telephone number:** Vergiftungs-Informations-Zentrale Freiburg  
Tel: +49 (0)761 19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.


Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**epoxy resin (number average molecular weight  $\leq$  700), reaction product: bisphenol-A-(epichlorhydrin)

Bisphenol-F-Epoxy resin

**Signal word:** Warning**Pictograms:****Hazard statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**5 Min. Epoxy (resin)**

Revision date: 16.03.2018

Product code: 155105

Page 2 of 9

**Precautionary statements**

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P273 Avoid release to the environment.
- P280 Wear protective gloves and eye/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

**Special labelling of certain mixtures**

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			50-100%
	500-033-5	603-074-00-8		
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H319 H315 H317 H411			
55492-52-9	Bisphenol-F-Epoxy resin			25-50%
	611-275-7			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated clothing immediately.

**After inhalation**

consult a doctor.

**After contact with skin**

Washing places concerned with a lot of water and soap. If the symptom doesn't stop, consult doctor.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Seek medical advice immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 5 Min. Epoxy (resin)

Revision date: 16.03.2018

Product code: 155105

Page 3 of 9

### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water spray jet  
Fight major fires with a water spray jet or alcohol-resistant foam.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Non-flammable. In case of fire: Formation of: Gases/vapours, toxic.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.  
Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate room ventilation, if necessary with vapour extraction at the workplace.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container. Provide for retaining containers, eg. floor pan without outflow.

#### Advice on storage compatibility

Store separately from foodstuffs.

#### Further information on storage conditions

Keep receptacles tightly sealed.

### 7.3. Specific end use(s)

Epoxy resin products, solvent-free, sensitising

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### 8.2. Exposure controls

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**5 Min. Epoxy (resin)**

Revision date: 16.03.2018

Product code: 155105

Page 4 of 9

**Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: NBR (Nitrile rubber), FKM (fluoro rubber), PVC (polyvinyl chloride)

Thickness of the glove material: > 0,5 mm

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

Combination filtering device (EN 14387): A-P2

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	characteristic

	Test method
pH-Value:	not determined
<b>Changes in the physical state</b>	
Melting point:	not determined
Initial boiling point and boiling range:	> 200 °C
Flash point:	> 200 °C
<b>Flammability</b>	
Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
<b>Auto-ignition temperature</b>	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
<b>Oxidizing properties</b>	
Not oxidising.	
Vapour pressure:	not determined

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**5 Min. Epoxy (resin)**

Revision date: 16.03.2018

Product code: 155105

Page 5 of 9

Density: 1,18 g/cm<sup>3</sup> ISO 2811

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

**Solubility in other solvents**

not determined

Partition coefficient: not determined

Viscosity / dynamic: 12000 mPa·s ISO 3219  
(at 23 °C)

Vapour density: not determined

Evaporation rate: not determined

**9.2. Other information**

Solid content: not determined

**SECTION 10: Stability and reactivity****10.1. Reactivity**

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

**10.2. Chemical stability**

no decomposition when stored and handled properly

**10.3. Possibility of hazardous reactions**

reaction with strong oxidising agents Alkali (lye) ,Acids

**10.4. Conditions to avoid**

none

**10.5. Incompatible materials**

Strong oxidizing agents.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)				
	oral	LD50 mg/kg	11400	Rat	GESTIS
	dermal	LD50 mg/kg	> 22800	Rabbit	GESTIS
55492-52-9	Bisphenol-F-Epoxy resin				
	oral	LD50 mg/kg	> 5000	Rat	

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5 Min. Epoxy (resin)

Revision date: 16.03.2018

Product code: 155105

Page 6 of 9

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)					
	Acute fish toxicity	LC50	4,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	EPA-660/3-75-009
	Acute algae toxicity	ErC50	9,4 mg/l	72 h	Scenedesmus capricornutum	EPA-660/3-75-009
	Acute crustacea toxicity	EC50	2,8 mg/l	48 h	Daphnia magna	OECD 202
	Acute bacteria toxicity	> 100 mg/l)		3 h	Activated sludge	

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)			
	OECD 301F	5%	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			
	OECD 301B	6-12%	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			

### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	3,24

#### BCF

CAS No	Chemical name	BCF	Species	Source
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	31		Quantitative structure-activity relationship (QSAR)

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**5 Min. Epoxy (resin)**

Revision date: 16.03.2018

Product code: 155105

Page 7 of 9

according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

**Waste disposal number of contaminated packaging**


080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide derivatives mw <=700)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Classification code: M6  
 Special Provisions: 274 335 601  
 Limited quantity: 5 L  
 Transport category: 3  
 Hazard No: 90  
 Tunnel restriction code: E

**Other applicable information (land transport)**

E1

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide derivatives mw <=700)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Classification code: M6  
 Special Provisions: 274 335 601  
 Limited quantity: 5 L

**Other applicable information (inland waterways transport)**

E1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5 Min. Epoxy (resin)

Revision date: 16.03.2018

Product code: 155105

Page 8 of 9

#### Marine transport (IMDG)

**14.1. UN number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
 (Epoxide derivatives mw <=700)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Marine pollutant: Ja  
 Special Provisions: 274, 335  
 Limited quantity: 5 L  
 EmS: F-A, S-F

#### Other applicable information (marine transport)

E1

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
 (Epoxide derivatives mw <=700)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
 Hazard label: 9



Special Provisions: A97 A158  
 Limited quantity Passenger: 30 kg G  
 IATA-packing instructions - Passenger: 964  
 IATA-max. quantity - Passenger: 450 L  
 IATA-packing instructions - Cargo: 964  
 IATA-max. quantity - Cargo: 450 L

#### Other applicable information (air transport)

E1

Passenger-LQ: Y964

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: epoxy resin (number average molecular weight <= 700), reaction product:  
 bisphenol-A-(epichlorhydrin)

#### 14.6. Special precautions for user

No information available.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**5 Min. Epoxy (resin)**

Revision date: 16.03.2018

Product code: 155105

Page 9 of 9

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

Regulation (EC) No. 2037/2000 concerning materials, which cause damage to the ozone layer.

Regulation (EC) No. 648/2004 (Detergents regulation)

**National regulatory information**

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	2 - clearly water contaminating
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*